

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 October 2005 (27.10.2005)

PCT

(10) International Publication Number
WO 2005/100465 A1

(51) International Patent Classification⁷: C08K 7/06, C08J 5/04, C08L 101/00, H01B 1/00, 1/24, 5/16

(21) International Application Number:
PCT/JP2005/007572

(22) International Filing Date: 14 April 2005 (14.04.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

2004-120429	15 April 2004 (15.04.2004)	JP
2004-120430	15 April 2004 (15.04.2004)	JP
2004-120431	15 April 2004 (15.04.2004)	JP
60/564,969	26 April 2004 (26.04.2004)	US
60/564,972	26 April 2004 (26.04.2004)	US
60/564,974	26 April 2004 (26.04.2004)	US
2004-243740	24 August 2004 (24.08.2004)	JP
60/605,508	31 August 2004 (31.08.2004)	US

(71) Applicant (for all designated States except US): SHOWA DENKO K. K. [JP/JP]; 13-9, Shiba Daimon 1-chome, Minato-ku, Tokyo 105-8518 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): NAGAO, Yuji [JP/JP]; c/o Corporate R & D Center, Showa Denko K.K., 5-1, Okawacho, Kawasaki-ku, Kawasaki-shi, Kanagawa

210-0858 (JP). YAMAMOTO Ryuji [JP/JP]; c/o Corporate R & D Center, Showa Denko K.K., 5-1, Okawacho, Kawasaki-ku, Kawasaki-shi, Kanagawa 210-0858 (JP).

(74) Agent: OHIE, Kunihsa; Ohie Patent Office, Selva-Ningyocho 6F, 14-6, Nihonbashi-Ningyocho, 2-chome, Chuo-Ku, Tokyo 103-0013 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CARBON-BASED ELECTRICALLY CONDUCTING FILLER, COMPOSITION AND USE THEREOF

(57) Abstract: A conductive composition comprising a vapor grown carbon fiber having an aspect ratio of 40 to 1,000, preferably 65 to 1,000, and a specific surface area or fiber diameter of the fiber within a predetermined range, and a preferable peak intensity ratio ($I_0 = I_{1360}/I_{1580}$) of 0.1 to 1, wherein I_{1580} represents a peak height at 1,580 cm^{-1} and I_{1360} represents a peak height at 1,360 cm^{-1} in a Raman scattering spectrum; and a resin composition containing the composition; and a production method thereof. The present invention provides: i) a composition which exhibits stable conductivity and less deterioration in physical properties during any molding methods in a conductive plastic in which a conductive filler is dispersed in a polymer; ii) a composite material composition for precision molding which enables production of a molded product with low warpage and is excellent in mechanical properties and performance during the injection molding; and iii) a sliding member composition which exhibits durability under high temperature and heavy load and has a low friction coefficient.



WO 2005/100465 A1